

Compact Bench Mounted Ductless Fume Cupboard

Circulaire 650



With optional spillage tray

The Circulaire 650 is a brand new addition to the popular Circulaire range of ductless fume cupboards.

The Circulaire 650 footprint is only 600mm x 650mm so takes up minimal bench space, but has the carbon filter capacity of a much larger unit. The supplied 14kg deep bed carbon filter will be matched specifically to your application to ensure the best possible containment. Filter types available are listed overleaf.

In addition to the compact footprint, the Circulaire 650 also boasts a large working aperture, integral low airflow alarm, low operating noise level, cable entry port and a unique carbon filter sealing mechanism with safe pre-filter change system.

The folding acrylic sash allows excellent access to the work area and overhead lighting ensures the work is well lit and easy to work in. Finally, the Circulaire 650 is manufactured from Epoxy coated Zintec steel to ensure years of uninterrupted service.

Monmouth
Scientific

Monmouth Scientific

Units 5 & 6, Kilnside, East Quay,
Bridgwater, Somerset TA6 4DB, United Kingdom
Tel: +44 (0)1278 458090 Fax: +44 (0)1278 458091
Email: info@monmouthscientific.co.uk
Monmouth Scientific is a trading division of Monmouth Surgical Ltd.



Compact Bench Mounted Ductless Fume Cupboard

Circulaire 650



Low airflow alarm



Control/alarm panel



Cable entry port



Optional deep lipped spillage tray

- Compact Design – just 650mm x 600mm
- 14kg Activated Carbon Filter (matched to your application)
- Integral low airflow alarm with audible and visual alarm
- Overhead lighting for maximum illumination of the working area
- Optional deep lipped spillage tray
- Side mounted cable entry port to allow safe use of electrical apparatus
- Safe and easy pre-filter change system
- Steel construction for years of uninterrupted use

Carbon Filter Types

AC	General organic compounds (i.e. elemental iodine, solvents, odours etc)
ACID	Acidic compounds (and general organics)
ACR	Alkali compounds (and general organics)
AMM	Ammonia & Amine containing compounds (and general organics)
CYN	Cyanide compounds (and general organics)
ETHER	Ether compounds (and general organics)
FORM	Aldehydes (and general organics)
SUL	Sulphur compounds (and general organics)
MCH	Special blend of up to 4 of the above carbon types
ED	Tri-Layered Filter for schools (organic, acid & alkali removed)

Specifications:

External Dimensions mm (WxDxH):	650 x 600 x 1082
Internal Dimensions mm (WxDxH):	600 x 600 x 760
Working Aperture mm (WxH):	590 x 300
Face Velocity:	0.5 m/sec
Airflow:	320 m ³ /hr
Filter Size mm (WxDxH):	600 x 400 x 115
Filter Weight	14kg
Pre-Filter:	Filtrete
Internal Lighting:	18 watt fluorescent
Fan:	Centrifugal, Brushless & Sparkless
Noise Level:	<55 db(A)
Electrical Supply:	230v - 400watts
Construction:	Head: Epoxy Powder Coated Zintec Steel Base: Epoxy Powder Coated Zintec Steel frame with 6mm clear acrylic front and side panels
Options:	GRP Spillage Tray

**Monmouth
Scientific**

Monmouth Scientific

Units 5 & 6, Kilnside, East Quay,
Bridgwater, Somerset TA6 4DB, United Kingdom
Tel: +44 (0)1278 458090 Fax: +44 (0)1278 458091
Email: info@monmouthscientific.co.uk
Monmouth Scientific is a trading division of Monmouth Surgical Ltd.

