



MA35

Rugged, Fully Automatic Infrared Moisture Analyzer for Use in Routine Operation

Advantages

- Time-saving alternative to a drying oven – measurement results in only 10–20 minutes
- Simple operation
- Rugged design
- Ideal for simple routine checks
- Best price-performance ratio with Sartorius quality – Made in Germany



Product Description

The MA35 is the ideal basic model for quick and reliable analysis of the material moisture of liquid, pasty and solid substances using the thermogravimetric method. Sartorius's decades of experience in the area of moisture analysis guarantees quick and reliable measurement results and high user-friendliness.

Applications

Ruggedness for All Areas of Application

The compact and rugged design, combined with great precision and measurement accuracy, make the MA 35 the ideal device for uniform measuring tasks. The selection of long-lasting and rugged components, impervious to vibration and dirt, guarantees reliable measurement results, even in a harsh environment. An ideal partner for use in production, incoming goods or in the laboratory.

Simple Use

Sartorius's unique, fully automatic endpoint determination makes programming a switch-off criterion unnecessary. This saves time because, on the one hand, time-consuming optimizations are no longer required, and on the other, operation of the device is simplified so that it can be used competently by anyone. This is made possible by continuous monitoring of the drying cycle by the MA35.

This monitoring then completes the measurement fully automatically using a switch-off criterion that is calculated based on the drying curve as soon as the sample weight is constant, and where despite heating, no additional loss of weight is detectable. The measurement accuracy required for this is provided by a Sartorius weighing system with readability to 1 mg, which has been specially optimized for use in high temperature ranges.

Quick Measurement Results

For sample heating, the MA35 features two powerful metal tubular-shaped heating elements generating 360 watts of power. These elements facilitate quick and uniform heating of samples and thus shorten measurement times, which means a significant amount of time is saved compared to the drying oven because the finished end result can already simply be read within a few minutes.

Technical Specifications

Weighing range	35 g
Typical reproducibility of the weighing system	From around 1 g of weight of sample taken: $\pm 0.2\%$ From around 5 g of weight of sample taken: $\pm 0.05\%$
Readability	1 mg; 0.01%
Measurement display	% moisture, % dry mass, % ATRO, g residue
Typical sample quantity	5 – 15 g
Access to the sample compartment	– by lifting top with wide opening angle – with viewing window
Windscreen	Integrated windscreen
Switch-off criterion	Optional: – Fully automatic – Manual switch-off – Allotted time 0.1 – 99 min.
Heating program	Standard drying
Measurement program	The device is power failure-proof, so 1 program can be saved (parameter freely selectable)
Temperature setting	40 – 160 degrees Celsius in increments of 1 degree Celsius
Sample heating	Uniform with an Infrared dark radiator (metal tubular-shaped heating elements)
Measured value storage	Results are safely stored until the start of the next measurement
Log printout	– Non-adjustable GLP log for measurement results Calibration Adjustment – Paper-saving brief log for measurement results – An optionally available external printer is used for the printout (YDP20 YDP30)
Inspection equipment monitoring	External calibration by means of optionally available calibration weights; temperature adjustment using an optional adjustment set
User guidance	Through symbols that correspond to the selected functions
Language selection	English, German, French, Spanish, Italian, Russian
Data interface	RS232 C-S/V24-V28, 7 Data-bit (ASCII) 1 Parity-bit
Network frequency	50 60 Hz
Power consumption	max. 400 VA
Case dimensions (W × D × H)	224 × 366 × 191 mm
Weight	Approximately 5.8 kg

Models Available

MA35M-230N	Standard version 230 V +15%, -20%
MA35M-115N	Standard version 115 V +15%, -20%
MA35M-115US	Standard version 115 V +15%, -20% with country-specific enhancements for the USA
MA35M-1CN230V1	Standard version 230 V +15%, -20% with country-specific enhancements for China

Accessories

6965542	Disposable sample pans 80 units, Aluminum, round, 90 mm
6906940	Fiberglass filter for use with liquid, pasty and oily samples, 80 units
6906941	Fiberglass filter, for use with liquid and oily samples, soft Quality, 200 count, Ø 90 mm
YDS05MA	Glass panel replacement set Aluminum pane instead of glass to comply with FDA/HACCP guidelines (Conversion kit)
YDP20-OCE	Data printer
6906918	Color ribbon for measured value printer
6906937	Paper rolls for data printer, 5 items at 50 m
YSS43-02	External calibration weight, 30 g ± 0.3 mg DKD [Deutsche Kalibrierdienst; German Calibration Service] certificate
YTM15MA	Temperature adjustment set
YMD01B	Individual method development for the MA35 (including brief report)

Scope of Supply

- Moisture measuring device with data interface
- Network cable
- 80 Aluminum sample pans

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany
Sartorius Lab Instruments
GmbH & Co. KG
Otto-Brenner-Strasse 20
37079 Goettingen
Phone +49.551.308.0
Fax +49.551.308.3289

France & Suisse Romande
Sartorius France
2, rue Antoine Laurent de Lavoisier
ZA de la Gaudrée
91410 Dourdan
Phone +33.1.70.62.50.00
Fax +33.1.64.59.76.39

Austria
Sartorius Austria GmbH
Modecenterstrasse 22
1030 Vienna
Phone +43.1.7965760.0
Fax +43.1.7965760.24

Belgium
Sartorius Belgium N.V.
Rue Colonel Bourg 105
1030 Bruxelles
Phone +32.2.756.06.90
Fax +32.2.481.84.11

Finland & Baltics
Sartorius Biohit Liquid Handling Oy
Laippatie 1
00880 Helsinki
Phone +358.9.755.951
Fax +358.9.755.95.200

Hungary
Sartorius Hungária Kft.
Kagyló u. 5.
2092 Budakeszi
Phone +3623.457.227
Fax +3623.457.147

Ireland
Sartorius Ireland Ltd.
Unit 41, The Business Centre
Stadium Business Park
Ballycoolin Road
Dublin 11
Phone +353.1.8089050
Fax +353.1.8089388

Italy
Sartorius Italy S.r.l.
Via Torino 3/5
20814 Varedo (MB)
Phone +39.0362.5557.11
Fax +39.0362.5557.99

Netherlands
Sartorius Netherlands B.V.
Phone +31.30.60.53.001
Fax +31.30.60.52.917
info.netherlands@sartorius.com

Poland
Sartorius Poland sp.z o.o.
ul. Wrzesinska 70
62-025 Kostrzyn
Phone +48.61.6473830
Fax +48.61.6473839

Russian Federation
LLC "Sartorius RUS"
Vasilyevsky Island
5th line 70, Lit. A
199178 St. Petersburg
Phone +7.812.327.53.27
Fax +7.812.327.53.23

Spain & Portugal
Sartorius Spain, S.A.
Avda. de la Industria, 32
Edificio PAYMA
28108 Alcobendas (Madrid)
Phone Spain +34.913.586.095
Phone Portugal +351.800.855.800
Fax Spain +34.913.589.623
Fax Portugal +351.800.855.799

Switzerland
Sartorius Mechatronics Switzerland AG
Ringstrasse 24a
8317 Tagelswangen (ZH)
Phone +41.44.746.50.00
Fax +41.44.746.50.50

U.K.
Sartorius UK Ltd.
Longmead Business Centre
Blenheim Road, Epsom
Surrey KT19 9QQ
Phone +44.1372.737159
Fax +44.1372.726171

Ukraine
LLS "Sartorius RUS"
Post Box 440 "B"
01001 Kiev, Ukraine
Phone +380.44.411.4918
Fax +380.50.623.3162

Americas

USA
Sartorius Corporation
5 Orville Drive, Suite 200
Bohemia, NY 11716
Phone +1.631.254.4249
Toll-free +1.800.635.2906
Fax +1.631.254.4253

Argentina
Sartorius Argentina S.A.
Int. A. Ávalos 4251
B1605ECS Munro
Buenos Aires
Phone +54.11.4721.0505
Fax +54.11.4762.2333

Brazil
Sartorius do Brasil Ltda
Avenida Senador Vergueiro 2962
São Bernardo do Campo
CEP 09600-000 - SP- Brasil
Phone +55.11.4362.8900
Fax +55.11.4362.8901

Canada
Sartorius Canada Inc
1173 North Service Road West, D4
Oakville, ON L6M 2V9
Phone +1.905.569.7977
Toll-Free +1.800.668.4234
Fax +1.905.569.7021

Mexico
Sartorius de México, S.A. de C.V.
Libramiento Norte de Tepotzotlan s/n,
Colonia Barrio Tlacateco,
Municipio de Tepotzotlan,
Estado de México,
C.P. 54605
Phone +52.55.5562.1102
Fax +52.55.5562.2942
leadsmex@sartorius.com

Peru
Sartorius Peru S.A.C.
Avenue Alberto del Campo 411
Floor 12 - The Office
15076 - San Isidro, Lima
Phone +51.1.441 0158
Fax +51.1.422 6100

Asia | Pacific

Australia
Sartorius Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175
Phone +61.3.8762.1800
Fax +61.3.8762.1828

China
Sartorius (Shanghai) Trading Co., Ltd.
3rd Floor, North Wing, Tower 1
No. 4560 Jinke Road
Zhangjiang Hi-Tech Park
Pudong District
Shanghai 201210, P.R. China
Phone +86.21.6878.2300
Fax +86.21.6878.2882

Hong Kong
Sartorius Hong Kong Ltd.
Unit 1012, Lu Plaza
2 Wing Yip Street
Kwun Tong
Kowloon, Hong Kong
Phone +852.2774.2678
Fax +852.2766.3526

India
Sartorius Weighing India Pvt. Ltd.
#69/2-69/3, NH 48, Jakkasandra,
Nelamangala Tq
562 123 Bangalore, India
Phone +91.80.4350.5250
Fax +91.80.4350.5253

Japan
Sartorius Japan K.K.
4th Fl., Daiwa Shinagawa North Bldg.
8-11, Kita-Shinagawa 1-chome
Shinagawa-ku, Tokyo, 140-0001 Japan
Phone +81.3.3740.5408
Fax +81.3.3740.5406

Malaysia
Sartorius Malaysia Sdn. Bhd
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur, Malaysia
Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore
Sartorius Singapore Pte. Ltd
10 Science Park Rd
The Alpha #02-13/14
Singapore Science Park II
Singapore 117684
Phone +65.6872.3966
Fax +65.6778.2494

South Korea
Sartorius Korea Ltd.
8th Floor, Solid Space B/D,
PanGyoYeok-Ro 220, Bundang-Gu
SeongNam-Si, GyeongGi-Do, 463-400
Phone +82.31.622.5700
Fax +82.31.622.5799

Thailand
Sartorius (Thailand) Co. Ltd.
129 Rama 9 Road,
Huaykwang
Bangkok 10310
Phone +66.2643.8361-6
Fax +66.2643.8367



◀ www.sartorius.com